UNCLASSIFIED CONFIDENTIAL 11038 SECRET Approved For Release 2003/12/04 : CPATROP78B05171A00010001010143-0 CONTRACT INSPECTION REPORT 25X1 T0: INSPECTION REPORT NO. (If final, so state) ESTIMATED COMPLETION DATE 15 March 1970 NAME OF CONTRACTOR THE CONTRACTOR WILL PROBABLY REMAIN WITHIN ALLOCATED

OMMENDATION AND/OR ACTION OF SPONSORING OFFICE, ON

OMMENDATION AND/OR ACTION OF SPONSORING OFFICE, ON REVERSE HEREOF. IF KNOWN. INDICATE MAGNITUDE OF AD-DITIONAL FUNDS INVOLVED. PER CENT OF WORK COMPLETED . PER CENT OF FUNDS EXPENDED . HAS AN INTERIM REPORT. FINAL REPORT. PROTOTYPE, OR OTHER END ITEM BEEN RECEIVED FROM THE CONTRACTOR

NG THE PERIOD? YES NO (If yes, give details on reverse side.)

HAS GOVERNMENT-OWNED PROPERTY BEEN DELIVERED TO CONTRACTOR DURING THIS PERIOD?

YES NO DURING THE PERIOD? (If yes, indicate items, quantity, and cost on reverse side.) INCENTIVES □ NO IS THIS AN INCENTIVE CONTRACT YES USE REVERSE SIDE FOR COMMENTS. FINAL REPORT MUST CONTAIN INCENTIVE EVALUATION. IF YES, CHECK TYPE PERFORMANCE DELIVERY COST AWARD OVERALL PERFORMANCE OF CONTRACTOR UNSATISFACTORY ABOVE AVERAGE OUTSTANDING AVERAGE EXCELLENT 2. MINIMUM ACCEPTABLE VERY GOOD IF OVERALL PERFORMANCE OF CONTRACTOR IS UNSATISFACTORY OR MINIMUM ACCEPTABLE INDICATE REASONS ON REVERSE SIDE. RECOMMENDED ACTION WITHHOLD PAYMENT PENDING CONTINUE AS PROGRAMMED SATISFACTORY PERFORMANCE OTHER (Specify) CLOSE OUT IF THIS IS A FINAL REPORT PUT COMMENTS ON REVERSE IN NARRATIVE FORM ON CONTRACTOR'S PERFORMANCE AND CERTIFY THAT ALL DELIVERABLE ITEMS UNDER THE CONTRACT HAVE BEEN RECEIVED. THESE INCLUDE, WHERE APPLICABLE, THE FOLLOWING: DOES NOT DOES NOT REC 1D ITEM REC 1D ITEM APPLY MANUALS PROTOTYPES FINAL REPORT DRAWINGS AND SPECIFICATIONS SPECIAL TOOLING PRODUCTION AND/OR OTHER OTHER GOVERNMENT PROPERTY END ITEMS DATE OF LAST CONTACT WITH CONTRACTOR **Declass Review by NIMA/DOD** 3-5 December 1968 DIVICION

Approved For Release 2003/12/04 : CIA-RDP78B05171A000100010143-0

UNCLASSIFIED

X CONFIDENTIAL

SÉCRET

(12 - 36)

25X1

25X1

FORM 1897 PREVIOUS EDITION

SECRET			i
	Approxed For Release 2003/12/04 : CIA-RDP78B05171A0001000	101 43 -P _{INAL}	
this inclu Attention origin project me time lost to complet for vacati able to be always our place in f	the front of this sheet, the percent of funds expended is iden 30% expended and 36% obligated. Intion is also called to the new estimated completion date and date was I Petruary 1970. Buring the last monitor to magor attempted to work out a realistic schedule to came and the delays resulting from the Ceneral Strike the optical system the end of July 1969 but their ention the month of August and, therefore, any rejected come reworked until September is working on the annumenthing that will have to be reworked and, therefore, and september. The entire program thereby slipping the complements.	e of 15 March 1970 rip to	2!
Meren 1970 The I	tochnical monitor. Mesersof IKO/PK visited thefacility on 3 & 4 December 1956Most	D, and of	
was a series	on system performance and computer programming	appears to o	翎 つり
PÖÄ to be ! Eleal gysi	completed. has revorked the PERT program to reflect the new complet ten is the critical path and limiting item for the entir	don date. The op-	1
30% york	comleted recerted reflects the new collectio.		۱.,
	pur completed the editest plices and purbled to en	in the second se	12
in France Sec. and	has completed the optical bridge and shipped it to ed a test susembly of coment with metal fixtures endeding the the comparator and support the optical bridge. An al	d in it. This is	
to simulation from the same ships the same ships the same ships the same same same same same same same sam	ed a test susembly of coment with metal fixtures endedding the the comparator and support the optical bridge. An allianed by to insure that the optical bridge and grant and aligned whether set up in or Yest on her tooling with pine and will use midrometers, depth	d in it. This is ligament device has to vill be properlington. The sligs aganges, etc. to	2
to simulation from the following to the rest to the re	ed a test ausembly of coment with metal fixtures endeddente the comparator and support the optical bridge. An all ioned by to insure that the optical bridge and grant and aligned whether set up in or Yest on two tooling with pine and will use midrometers. depth	dir it. This is interpreted to the control of the c	2
to simulation from from from from from from tor from nisent contract from the from the from the from f	ed a test susembly of coment with metal fixtures endedded to the comparator and support the optical bridge. An allianed by to insure that the optical bridge and gradies and aligned whether set up in or Yest ce has tooling with pine and will use micrometers, depting telerances in all cases. has submitted a format: it proposes for: (1) Operator's ing Hamuel, and (3) Service Manuel. These will be revisioned to with comments. has requested that MPIC specify the test targets and make final acceptance tests for the optical system. The stand that the Test and Evaluation component provide this	dir it. This is interpreted to the control of the c	2
to simulation from the following to the rest to the re	ed a test susembly of coment with metal fixtures endedded to the comparator and support the optical bridge. An allianed by to insure that the optical bridge and gradies and aligned whether set up in or Yest ce has tooling with pine and will use micrometers, depting telerances in all cases. has submitted a format: it proposes for: (1) Operator's ing Hamuel, and (3) Service Manuel. These will be revisioned to with comments. has requested that MPIC specify the test targets and make final acceptance tests for the optical system. The stand that the Test and Evaluation component provide this	dir it. This is ligament device has its vill be properly ington. The slight gauges, etc. to with the cognical shat will becomical monitors information at an	2
to simulation from the following to the rest to the re	ed a test susembly of coment with metal fixtures ended to the comparator and support the optical bridge. An allianed by to insure that the optical bridge and gradical and aligned whether set up in or Washes tooling with pine and will use midromaters, depting telegrances in all cases. The submitted a format: it proposes for: (1) Operator's ing Hannel, and (3) Service Manuel. These will be revisioned to with comments. The requested that MPIC specify the test targets and make final acceptance tests for the optical system. The stand that the Test and Syslustical component provide this stand that the Test and Syslustical component provide this can apply the same tests to	dir it. This is ligament device has its vill be properly ington. The slight gauges, etc. to with the cognical shat will becomical monitors information at an	2
to simulation from from from from from from tor from nisent contract from the from the from the from f	ed a test susembly of coment with metal fixtures ended to the comparator and support the optical bridge. An allianed by to insure that the optical bridge and gradical and aligned whether set up in or Washes tooling with pine and will use midromaters, depting telegrances in all cases. The submitted a format: it proposes for: (1) Operator's ing Hannel, and (3) Service Manuel. These will be revisioned to with comments. The requested that MPIC specify the test targets and make final acceptance tests for the optical system. The stand that the Test and Syslustical component provide this stand that the Test and Syslustical component provide this can apply the same tests to	dir it. This is ligament device has its vill be properly ington. The slight gauges, etc. to with the cognical shat will becomical monitors information at an	2:
to simulation from from from from from from tor from nisent contract from the from the from the from f	ed a test susembly of coment with metal fixtures ended to the comparator and support the optical bridge. An allianed by to insure that the optical bridge and gradical and aligned whether set up in or Washes tooling with pine and will use midromaters, depting telegrances in all cases. The submitted a format: it proposes for: (1) Operator's ing Hannel, and (3) Service Manuel. These will be revisioned to with comments. The requested that MPIC specify the test targets and make final acceptance tests for the optical system. The stand that the Test and Syslustical component provide this stand that the Test and Syslustical component provide this can apply the same tests to	dir it. This is ligament device has its vill be properly ington. The slight gauges, etc. to with the cognical shat will becomical monitors information at an	2
to simulation from from from from from from tor from nisent contract from the from the from the from f	ed a test susembly of coment with metal fixtures ended to the comparator and support the optical bridge. An allianed by to insure that the optical bridge and gradical and aligned whether set up in or Washes tooling with pine and will use midromaters, depting telegrances in all cases. The submitted a format: it proposes for: (1) Operator's ing Hannel, and (3) Service Manuel. These will be revisioned to with comments. The requested that MPIC specify the test targets and make final acceptance tests for the optical system. The stand that the Test and Syslustical component provide this stand that the Test and Syslustical component provide this can apply the same tests to	dir it. This is ligament device has its vill be properly ington. The slight gauges, etc. to with the cognical shat will becomical monitors information at an	2
to simulation from from from from from from tor from nisent contract from the from the from the from f	ed a test susembly of coment with metal fixtures ended to the comparator and support the optical bridge. An allianed by to insure that the optical bridge and gradical and aligned whether set up in or Washes tooling with pine and will use midromaters, depting telegrances in all cases. The submitted a format: it proposes for: (1) Operator's ing Hannel, and (3) Service Manuel. These will be revisioned to with comments. The requested that MPIC specify the test targets and make final acceptance tests for the optical system. The stand that the Test and Syslustical component provide this stand that the Test and Syslustical component provide this can apply the same tests to	dir it. This is ligament device has its vill be properly ington. The slight gauges, etc. to with the cognical shat will becomical monitors information at an	2

25X1

25X1

25X1

25X1

25X1

25X1

25X1 25X1

25X1